



SAFETY DATA SHEET

Gator Oil Cutter Bar Oil (ET30)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Gator Oil Cutter Bar Oil (ET30)
Product number	7765-606
Internal identification	GHS23491

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cutter Oil
Uses advised against	No specific uses advised against are identified. Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier	Morris Lubricants Castle Foregate Shrewsbury Shropshire SY1 2EL +44 (0) 1743 232200 +44 (0) 1743 353584 sds@morris-lubricants.co.uk
----------	--

1.4. Emergency telephone number

Emergency telephone	+44(0)1743 232200 (08.45 - 17.00 GMT)
---------------------	---------------------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Not Classified

Classification (67/548/EEC or 1999/45/EC) -

2.2. Label elements

Hazard statements	EUH208 Contains Calcium long chain alkaryl sulphonate. May produce an allergic reaction.
Precautionary statements	P501a Dispose of contents/container to hazardous or special waste collection point.
Supplemental label information	EUH210 Safety data sheet available on request.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Gator Oil Cutter Bar Oil (ET30)

Distillates (petroleum) solvent-dewaxed heavy paraffinic	30-60%
CAS number: 64742-54-7	EC number: 265-157-1
	REACH registration number: 01-2119484627-25-XXXX
A petroleum product. DMSO extract < 3 % weight (IP 346)	
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -
Phosphorodithioic acid,mixed 0,0-bis(1,3-dimethylbutyl and iso-Pr)esters,zinc salts	<1%
CAS number: 84605-29-8	EC number: 283-392-8
	REACH registration number: 01-2119493626-26-XXXX
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xi;R38,R41. N;R51/53.
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl)-bis(phosphorodithioate)	<1%
CAS number: 2215-35-2	EC number: 218-679-9
	REACH registration number: 01-2119953275-34-XXXX
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xi;R38,R41. N;R51/53.
2,6-di-tert-butyl-p-cresol	<1%
CAS number: 128-37-0	EC number: 204-881-4
	REACH registration number: 01-2119555270-46-0000
M factor (Acute) = 1	M factor (Chronic) = 1
Classification Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC or 1999/45/EC) N;R50/53.

Gator Oil Cutter Bar Oil (ET30)

Phenol, dodecyl-, branched <1%		
CAS number: 121158-58-5	EC number: 310-154-3	REACH registration number: 01-2119513207-49-XXXX
M factor (Acute) = 10	M factor (Chronic) = 10	

Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Corr. 1C - H314	Repr. Cat. 3;R62. Xi;R36/38. N;R50/53.
Eye Dam. 1 - H318	
Repr. 1B - H360F	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

Diphenylamine <1%		
CAS number: 122-39-4	EC number: 204-539-4	REACH registration number: 01-2119488966-13-0000
M factor (Acute) = 1	M factor (Chronic) = 1	

Classification	Classification (67/548/EEC or 1999/45/EC)
Acute Tox. 3 - H301	T;R23/24/25. N;R50/53. R33.
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT RE 2 - H373	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Get medical attention if any discomfort continues. Do not induce vomiting.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

Gator Oil Cutter Bar Oil (ET30)

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours. Heat from fire could result in drums bursting

5.3. Advice for firefighters

Protective actions during firefighting Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions In case of spills, beware of slippery floors and surfaces. For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Distillates (petroleum) solvent-dewaxed heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Short-term exposure limit (15-minute): ACGIH 10 mg/m³

Diphenylamine

Short-term exposure limit (15-minute): WEL 20 mg/m³

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

WEL = Workplace Exposure Limit.

Ingredient comments WEL = Workplace Exposure Limits

Gator Oil Cutter Bar Oil (ET30)

Phosphorodithioic acid,mixed 0,0-bis(1,3-dimethylbutyl and iso-Pr)esters,zinc salts (CAS: 84605-29-8)

DNEL	Industry - Dermal; Long term systemic effects: 12.1 mg/kg Industry - Inhalation; Long term systemic effects: 8.31 mg/m ³ Consumer - Dermal; Long term systemic effects: 6.1 mg/kg Consumer - Inhalation; Long term systemic effects: 2.11 mg/m ³ Consumer - Oral; Long term systemic effects: 0.24 mg/kg
PNEC	- Fresh water; 0.004 mg/l - marine water; 0.0046 mg/l - Soil; 0.0548 mg/kg

Diphenylamine (CAS: 122-39-4)

DNEL	Workers - Dermal; Long term systemic effects: 0.62 mg/kg Workers - Inhalation; Long term systemic effects: 4.37 mg/m ³ Consumer - Dermal; Long term systemic effects: 0.31 mg/kg Consumer - Inhalation; Long term systemic effects: 1.09 mg/m ³ Consumer - Oral; Long term systemic effects: 0.31 mg/kg
PNEC	- Fresh water; 0.051 mg/l - marine water; 0.0051 mg/l - Intermittent release; 0.51 mg/l - Sediment (Freshwater); 9320 mg/kg - Sediment (Marinewater); 932 mg/kg - Soil; 1860 mg/kg - STP; 1 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact. Use of suitable barrier/afterwork creams to protect skin may be beneficial.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Do not eat, drink or smoke when using this product.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

Gator Oil Cutter Bar Oil (ET30)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Amber.
Odour	Characteristic. Oil-like.
Odour threshold	Not determined.
pH	Not applicable.
Melting point	Not determined.
Initial boiling point and range	>320°C @ 101.3 kPa
Flash point	201°C Pensky-Martens closed cup.
Other flammability	Product is not flammable but on excessive heating may become combustible.
Vapour pressure	<0.1 kPa @ 20°C
Vapour density	Not determined.
Relative density	0.880 @ 15.6°C
Solubility(ies)	The product is insoluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	log Kow: > 7 This figure is typical of mineral oil.
Auto-ignition temperature	>320°C
Decomposition Temperature	Not determined.
Viscosity	85 cSt @ 40°C
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

Volatile organic compound	The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOCs may be present.
----------------------------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents.
---------------------------	--------------------------

10.6. Hazardous decomposition products

Gator Oil Cutter Bar Oil (ET30)

Hazardous decomposition products Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

Inhalation Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Causes serious eye irritation.

Acute and chronic health hazards Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

SECTION 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient log Kow: > 7 This figure is typical of mineral oil.

12.4. Mobility in soil

Mobility The product is non-volatile. The product is insoluble in water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. This material and its container must be disposed of as hazardous waste.

Disposal methods Dispose of waste via a licensed waste disposal contractor.

Waste class European waste catalogue (EWC) number = 13 02 05* (mineral based non-chlorinated engine, gear & lubricating oils)

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

Gator Oil Cutter Bar Oil (ET30)

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Special Waste regulations 1996.
EU legislation	Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	07/04/2021

Gator Oil Cutter Bar Oil (ET30)

Revision	2
Supersedes date	18/02/2019
SDS number	23491
Hazard statements in full	H301 Toxic if swallowed. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H331 Toxic if inhaled. H360F May damage fertility if swallowed. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH208 Contains Calcium long chain alkaryl sulphonate. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.