



Product Information:
GROUND FORCE CROMA 30
Chain Saw Cutter Bar Oil

Description

Groundforce Croma 30 Cutter Bar Oil is designed to meet all lumber industry, forestry, woodyard and estate management requirements. Provides excellent corrosion protection and improved chain performance in a wide range of climatic conditions.

Features

- Reduce wear on cutter bar chain and sprockets
- Reduce buildup of messy foam
- Resist tendency to fling from fast moving parts
- Allow use in subzero temperatures
- Provide excellent corrosion protection

Applications

Groundforce Croma 30 is recommended for use in all chain lubrication systems and should be used in accordance to manufacturer's recommendations. Where biodegradable oils are required or desirable, Terralus CBO should be selected.

Performance Levels

Groundforce Croma 30 is approved and endorsed by the British Agricultural & Garden Machinery Association.

Physical Characteristics

Appearance	Tacky Amber liquid
Density at 15.6 °C	0.880
Kinematic Viscosity at 100 °C (cSt)	15.2
Kinematic Viscosity at 40 °C (cSt)	128.2
Viscosity Index	120
Closed Flash Point (°C)	190
Pour Point (°C)	-30

Figures based on average production values.

Part No.s: GRO001, CRO005, CRO025, CRO205

(TDS Groundforce Croma 30 – 090818 Issue 5)

